

M A T E R I A L S A F E T Y D A T A S H E E T

EPOXY QUICK PATCH- PART A WHITE

PRODUCT NAME: EPOXY QUICK PATCH- PART A WHITE
PRODUCT CODE: EQP-A-0005

HMIS CODES: H F R P
2 1 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Polymerica Inc.
ADDRESS : 3821 Collins Lane
Louisville, KY 40245

EMERGENCY PHONE : 1-800-535-5053 DATE PRINTED : 4/1/08
INFORMATION PHONE : 1-800-762-1678

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (MM HG @ TEMP), WEIGHT PERCENT. Rows include Epoxy Phenol Novolac Resin, ALIPHATIC GLYCIDYL ETHER, Calcium Carbonate, Glass Oxide w/ coating, Titanium Dioxide, Siloxanes & Silicones, Benzyl Alcohol, and Acrylate Copolymer.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 400 F - 401 F SPECIFIC GRAVITY (H2O=1): 1.5224
VAPOR DENSITY: Not Determined. EVAPORATION RATE: Heavier than air (Air=1).

COATING V.O.C.: 0.0 lb/gl MATERIAL V.O.C.: 0.0 lb/gl
SOLUBILITY IN WATER: NIL.
APPEARANCE AND ODOR: Brown, stiff paste. Mild, no characteristic odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush at once with potable water for at least 15 minutes.
Skin: Wash with soap and warm water. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes.
Ingestion: Not likely to occur in normal handling. Give large quantities of water and get medical attention.
Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Avoid contact. Soak up with clay or other absorbent material.

WASTE DISPOSAL METHOD

Place in covered container for disposal. Dispose in an approved incinerator or an approved landfill in accordance with federal, state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use with good ventilation. Store in cool dry area. Keep containers tightly closed when not in use. Grinding or other abrasive action to cured film may develop microcrystalline silica dust. Wear a dust mask during such operations. If mixture A & B are allowed to remain in the mixing vessel past the pot life deadline, heat and a strong reaction will result.

OTHER PRECAUTIONS

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

None needed under normal conditions of use.

VENTILATION

Use good general mechanical ventilation and local exhaust.

PROTECTIVE GLOVES

Wear neoprene or natural rubber gloves.

EYE PROTECTION

NIOSH approved safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Body protection as necessary to prevent skin contact. Wash after handling. Provide eye wash fountain and safety shower.

WORK/HYGIENIC PRACTICES

Avoid breathing vapor mist or spray. Provide eye wash fountain and safety shower. Wash hands thoroughly after use, before eating or smoking.

===== SECTION IX - DISCLAIMER =====

The product information contained herein is believed to be accurate as of the date of the Material Safety Data Sheet, and is provided without warranty, expressed or implied, as to the results of use of this information or the product to which it relates. Recipient assumes all responsibility for the use of this information and the use (alone or in

M A T E R I A L S A F E T Y D A T A S H E E T

EPOXY QUICK PATCH- PART A WHITE

Page: 4

combination with any other product), storage or disposal of the product, including any resultant personal injury or property damage.