

M A T E R I A L   S A F E T Y   D A T A   S H E E T

Novolac Barrier Coat- Part A

Page: 1

PRODUCT NAME: Novolac Barrier Coat- Part A
PRODUCT CODE: NBC-A-2006

HMIS CODES: H F R P
2 1 0 C

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Polymerica, Inc.
ADDRESS : 3821 Collins Lane
Louisville, KY 40245

EMERGENCY PHONE : 1-800-535-5053 DATE PRINTED : 4/1/08
INFORMATION PHONE : 1-800-762-1678

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 5 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (MM HG @ TEMP), WEIGHT PERCENT, and additional details. Rows include Bisphenol A/Epichlorohydrin Based Epoxy Resin, Epoxy Phenol Novolac Resin, Phenol, 4-nonyl-, branched, Benzyl Alcohol, Di-n-butyl phthalate, Silicon Dioxide, Distillates (petroleum), hydrotreated light, Calcium Carbonate, Solvent naphtha, petroleum, light aromatic, and Acrylate Copolymer.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 225 F - 545 F SPECIFIC GRAVITY (H2O=1): 1.1724
VAPOR DENSITY: Not Determined. EVAPORATION RATE: Heavier than air (Air=1).

COATING V.O.C.: 0.0 lb/g1 MATERIAL V.O.C.: 0.0 lb/g1

**SOLUBILITY IN WATER: NIL.**

**APPEARANCE AND ODOR: Appearance: Moderately viscous liquid, color varies.**

**Odor: Mild, no characteristic odor.**

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

**FLASH POINT: 203 F**

**METHOD USED: SETAFLASH**

**FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.00000      UPPER: 12**

**EXTINGUISHING MEDIA: Use foam, dry chemical, CO2.**

**SPECIAL FIREFIGHTING PROCEDURES**

Material will not burn unless preheated. Clear fire area of all non-emergency personnel. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus. Cool surrounding equipment, fire-exposed containers and structures with water. Container areas exposed to direct flame contact should be cooled with large quantities of water (500 gallons water per minute flame impingement exposure) to prevent weakening of container structure.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Decomposition and/or products of combustion may be toxic.

===== SECTION V - REACTIVITY DATA =====

**STABILITY: Normally Stable.**

**CONDITIONS TO AVOID**

Avoid strong acids or bases in bulk and elevated temperatures.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Avoid contact with strong oxidizing agents, strong acids, strong bases.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Carbon monoxide, carbon dioxide, phenolic derivative.

**HAZARDOUS POLYMERIZATION: Mixing large quantities (1 gallon) with amines or epoxy hardeners can cause heat build-up and hazardous reaction.**

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Exposure to vapors at elevated temperatures may cause irritation to respiratory tract and difficulty breathing.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

May cause irritation.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

A single exposure is unlikely to result in harm. Repeated exposure can cause sensitization.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Oral toxicity is low. No hazards expected from normal industrial exposure.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

**CARCINOGENICITY:**    **NTP CARCINOGEN:**                    **IARC MONOGRAPHS:**                    **OSHA REGULATED:**

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Skin contact may aggravate an existing dermatitis (skin condition). Overexposure to vapor, dust or mist may aggravate existing respiratory conditions such as asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

**EMERGENCY AND FIRST AID PROCEDURES**

Eyes: Flush at once with potable water for at least 15 minutes.

Skin: Wash with soap and warm water. Remove contaminated clothes. Wash before reuse. Destroy contaminated shoes.

Ingestion: Not likely to occur in normal handling. Give large quantities of water and get medical attention.

Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult.

=====    **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**    =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Avoid contact. Soak up with clay or other absorbent material.

**WASTE DISPOSAL METHOD**

Place in covered container for disposal. Dispose in an approved incinerator or an approved landfill in accordance with federal, state and local regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Use with good ventilation. Store in cool dry area. Keep containers tightly closed when not in use. Grinding or other abrasive action to cured film may develop microcrystalline silica dust. Wear a dust mask during such operations. If mixture A & B are allowed to remain in the mixing vessel past the pot life deadline, heat and a strong reaction will result.

**OTHER PRECAUTIONS**

=====    **SECTION VIII - CONTROL MEASURES**    =====

**RESPIRATORY PROTECTION**

None needed under normal conditions of use.

**VENTILATION**

Use good general mechanical ventilation and local exhaust.

**PROTECTIVE GLOVES**

Wear neoprene or natural rubber gloves.

**EYE PROTECTION**

NIOSH approved safety glasses or goggles.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Body protection as necessary to prevent skin contact. Wash after handling. Provide eye wash fountain and safety shower.

**WORK/HYGIENIC PRACTICES**

Avoid breathing vapor mist or spray. Provide eye wash fountain and safety shower. Wash hands thoroughly after use, before eating or smoking.

===== SECTION IX - DISCLAIMER =====

The product information contained herein is believed to be accurate as of the date of the Material Safety Data Sheet, and is provided without warranty, expressed or implied, as to the results of use of this information or the product to which it relates. Recipient assumes all responsibility for the use of this information and the use (alone or in combination with any other product), storage or disposal of the product, including any resultant personal injury or property damage.

PRODUCT NAME: Novolac Barrier Coat- Part B  
 PRODUCT CODE: NBC-B-0000

HMIS CODES: H F R P  
 3 1 0 C

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Polymerica, Inc.  
 ADDRESS : 3821 Collins Lane  
 Louisville, KY 40245

EMERGENCY PHONE : 1-800-535-5053      DATE PRINTED : 4/1/08  
 INFORMATION PHONE : 800-762-1678

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE MM HG @ TEMP	WEIGHT PERCENT
----- TRIS (Dimethylaminomethyl) Phenol None Established	90-72-2	N/A	N/A
Phenol, 4-nonyl-, branched None Established	84852-15-3	5	310 F
Benzyl Alcohol Benzyl alcohol AIHA WEEL TWA- 10ppm, 44.2 mg/m3	100-51-6	0.15	68 F

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 390 F - 545 F      SPECIFIC GRAVITY (H2O=1): .9875  
 VAPOR DENSITY: Not Determined.      EVAPORATION RATE: Heavier than air  
 (Air=1).

COATING V.O.C.: 0.0 lb/gl      MATERIAL V.O.C.: 0.0 lb/gl  
 SOLUBILITY IN WATER: Partial.  
 APPEARANCE AND ODOR: Low viscosity, clear to amber liquid with sharp ammoniacal  
 type odor.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 210 F      METHOD USED: TCC  
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/D      UPPER: N/D

EXTINGUISHING MEDIA: Use foam, dry chemical, CO2.

SPECIAL FIREFIGHTING PROCEDURES  
 Wear positive pressure self-contained breathing equipment. Use water to cool containers exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS  
 Toxic fumes present when this material is in fire. Containers may rupture.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Normally Stable.

**CONDITIONS TO AVOID**

Avoid strong oxidizing agents and epoxy resins under uncontrolled conditions and elevated temperatures.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Avoid contact with acids such as Hydrochloric or Sulfuric. Avoid strong oxidizing agents and epoxy resins under uncontrolled conditions.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

When exposed to fire, oxides of carbon and nitrogen will be generated.

**HAZARDOUS POLYMERIZATION:**

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause severe irritation of respiratory tract.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Corrosive- Can cause burns, vapors can cause irritation.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Corrosive- Can cause burns.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause severe damage to mouth and throat.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

**CARCINOGENICITY:**    **NTP CARCINOGEN:**                    **IARC MONOGRAPHS:**                    **OSHA REGULATED:**

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Skin contact may aggravate an existing dermatitis (skin condition). Overexposure to vapor, dust or mist may aggravate existing respiratory conditions such as asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

**EMERGENCY AND FIRST AID PROCEDURES**

Eyes: Flush immediately for 15 minutes with large amounts of potable water. Get immediate medical attention.

Skin: Flush immediately for 15 minutes with potable water. Remove contaminated clothing. Launder before reuse.

Discard contaminated shoes. Get medical attention if swelling and/or irritation occurs.

Ingestion: DO NOT induce vomiting. Give milk or water to dilute stomach contents. Get immediate medical attention.

Inhalation: Remove to fresh air. Get medical attention if effects persist.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Avoid contact. Allow only personnel wearing goggles, neoprene or rubber gloves, and protective clothing to clean up spill. In confined areas a full face respirator is recommended. Absorb spill with clay, diatomaceous earth or other absorbent material.

**WASTE DISPOSAL METHOD**

Place in covered container for disposal. Dispose in an approved incinerator or an approved landfill in accordance with federal, state and local regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Mechanical ventilation required if TLV is expected to be exceeded in confined areas. Avoid contact. Keep containers tightly closed when not in use. Do not remove labels from empty containers. If mixtures A & B are allowed to remain in mixing vessel past pot life deadline, heat and a strong reaction will result.

**OTHER PRECAUTIONS**

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

None needed under normal conditions of use.

**VENTILATION**

Mechanical ventilation is required if TLV is expected to be exceeded in confined areas.

**PROTECTIVE GLOVES**

Wear neoprene or natural rubber gloves.

**EYE PROTECTION**

NIOSH approved safety glasses or goggles.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Body protection as necessary to prevent skin contact. Wash after handling. Provide eye wash fountain and safety shower.

**WORK/HYGIENIC PRACTICES**

Practice good industrial hygiene. Wash with soap and water before eating or smoking.

===== SECTION IX - DISCLAIMER =====

The product information contained herein is believed to be accurate as of the date of the Material Safety Data Sheet, and is provided without warranty, expressed or implied, as to the results of use of this information or the product to which it relates. Recipient assumes all responsibility for the use of this information and the use (alone or in combination with any other product), storage or disposal of the product, including any resultant personal injury or property damage.